



datasheet

autostereoscopic
 Multi-View 3D-display

MV2450va



Optical	Size (diagonal)	24" (61 cm)
	Size (active area)	518 x 324 mm
	Format	16:10 wide
	3D-views	5
	3D-technology	parallax-barrier
	Optimal viewing distance	approx. 0,7 m
	Pixel per view	1,38 Mio subpixels
	Native resolution (total)	WUXGA (1920 x 1200 RGB-Pixel)
	Native brightness of panel	400cd/m ² typ.
	Native contrast ratio	800:1
	Native colors	16,77 Mio (8bits RGB)
	Response time (ton+toff)	8 ms typ. (grey to grey)
	Panel technology	IPS TFT

Physical	Outer Dimensions (W x H x D)	557 x 362 x 107 mm (without stand) 557 x 430-580 x 306 mm (incl. stand)
	Weight	10,2 kg (without stand) 14,9 kg (incl. stand)
	Housing	rear cover: black plastic front bezel: stainless steel (brushed) bezel width: 18,5 mm
	Table stand	detachable height / tilt / swivel adjustable
	Wall mounting	VESA 100x100 / 200x100 (M4)
	Operating conditions	+ 5° - +35° C



		30%-80% rel. humidity (non-condensing)
	Storage conditions	-10° - +60° C 10% - 80% rel. humidity (non-condensing)
Electrical	Power input	100V - 240V AC / 1,2 A 50-60Hz
	Power consumption	85 W max.
	Signal inputs	DVI-D DVI-I analog HD-15
miscellaneous	Accessories	Power cord DVI-D to DVI-D signal cable DVI-A to HD-15 signal cable user manual
	Approvals	CE FCC <i>cBV_{us} (safety mark USA & Canada)</i>
	Software compatibility	Please contact TRIDELITY for detailed information
	Package dimensions (W x H x D)	685 x 605 x 455 mm
	Package weight	19,5kg

errors excepted / subject to change without notice
© 2009-2010 TRIDELITY Display Solutions GmbH